SET-UP SHEET

XT2'24 SET-UP SHEET VER. 1 ©XRAY 2024

XRAY XT2'24

RACE
TRACK
NAME DATE

LAPS | BEST LAP TIME sec
QUALIFYING POSITION | FINAL POSITION

TRACK

SIZE ☐ OPEN ☐ MEDIUM ☐ TIGHT
TRACTION ☐☐☐☐☐☐☐☐☐ VERY-LOW MEDIUM VERY-HIGH
SURFACE ☐ SMOOTH ☐ MEDIUM ☐ BUMPY
TYPE ☐ CLAY ☐ CARPET ☐ ASTRO
CONDITION ☐ BLUE GROOVE ☐ HARD PACKED ☐ DRY ☐ DUSTY ☐ LOAMY ☐ WET

TRANSMISSION

BALL DIFF ☐ GEAR DIFF ☐ ACTIVE DIFF ☐
DIFFERENTIAL OIL cSt ☐ 60° ☐ 90° ☐ 120°
SATELITE GEARS COMPOSITE ☐ ☐ STEEL GEARS 2 ☐ ☐ 4
SLIPPER 2 PAD ☐ ☐ 3 PAD ☐ mm
SLIPPER CLUTCH PLATES KIT ☐ ☐ VENTILATED SOLID AXLE ☐

GEAR BOX HARDNES

KIT ☐ ☐ GRAPHITE

GEARING

PINION T | SPUR GEAR T

SHOCKS

FRONT		REAR
	SPRINGS	
cSt	OIL	cSt
2 HOLES ☐	☐ ø1.6mm ☐ ø1.8mm	2 HOLES ☐
HOLES	ø mm ø mm	HOLES
Thickness 2.0mm ☐ 2.5mm Precision ☐ KIT	KIT ☐ ALU ☐	Thickness 2.0mm ☐ 2.5mm KIT ☐ Precision
DOWNSTOP SHIM INSERT UNDER PISTON	mm mm	DOWNSTOP SHIM INSERT UNDER PISTON
LENGTH	mm mm	LENGTH
UPSTOP SHIM INSERT ABOVE COLLAR	mm mm	UPSTOP SHIM INSERT ABOVE COLLAR
KIT ☐ ALU ☐ 0mm ☐ -2mm ☐ -4mm ☐	COLLAR	0mm ☐ -2mm ☐ -4mm ☐ KIT ☐ ALU ☐
☐ +4mm ☐ +2mm ☐ KIT	BALL JOINT	☐ KIT ☐ +2mm ☐ +4mm

ANTI ROLL BAR

FRONT mm | THICKNESS | REAR mm

TIRES

FRONT		REAR
	BRAND	
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS

MOTOR SPEEDO
MOTOR TIMING BATTERY

BODY

☐ LIGHT

TOTAL WEIGHT

/g

COMMENT

FRONT — APPLIED ◉ ☒ APPLIED — REAR

CASTER BLOCK: MEDIUM - KIT ☐ HARD GRAPHITE ☐ ALU ☐
ALU C-HUB: UP /mm DOWN /mm
STEERING BLOCK: MEDIUM - KIT ☐ HARD GRPHITE ☐ ALU ☐
LONGER BUSHINGS: UP ☐ DOWN ☐
CAMBER LINK LOCATION
LOWER SHOCK POSITION
SHIM mm
GRAPHITE SHOCK TOWER POSITION
SHIM /mm: MEDIUM - KIT ☐ HARD ☐ GRAPHITE ☐ ALU ☐
REAR UPRIGHT: HIGH ☐ LOW ☐
DRIVE SHAFT: KIT ☐ /mm
SHIM mm
LOWER SHOCK POSITION
#325341 ADJ. DRIVE AXLE

ARM MOUNT: 0° ☐ KIT 0° ☐ ALU -3° ☐ ALU +3° ☐ ALU 0° ☐ BRASS TOTAL KICK-UP°
STEERING BUMP STEER SHIM /mm
ACKERMANN SHIM /mm
CASTER BUSHINGS 0° ☐ 2.5° ☐ 5° ☐
KICK-UP°
ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP
FRONT

HIGH
WING: HIGH ☐ LOW ☐ OTHER /mm

FRONT TOE °
OFFSET /slots
WHEELBASE /mm
ROLL CENTER: KIT ☐ ALU ☐
STEERING: PLATE KIT ☐ ALU ☐ ARMS KIT ☐ ALU ☐
OUT
EXTENSION: 1 DOT ☐ 2 DOTS ☐ 3 DOTS ☐
SERVO POSITION
BATTERY PLACEMENT: LONG SIDE FRONT ☐ LONG SIDE REAR ☐
BATTERY SIZE: STD. SHORT ☐ LOW SHORT ☐
SERVO BRACE: YES ☐ NO ☐
SIDE BRACES: KIT ☐ ☐ GRAPHITE
REAR TOE ° IN
MOTOR PLATE: KIT ☐
UPPER BRACE: YES ☐ NO ☐
COOLING: FRONT ☐ ☐ REAR
OFFSET /slots
WHEELBASE /mm
ROLL CENTER: KIT ☐ GRAPHITE ☐ ALU ☐
REAR

REAR ROLL CENTER SUSPENSION HOLDERS
RF 0.5° ☐☐ 1° — 0mm ☐ ☐ 1mm
RR 0.5° ☐☐ 1° — XRAY 3° — 0mm ☐ ☐ 1mm
3° ☐ 1° KIT
Rasing the suspension holders with shims.
#323326 ALU REAR LOWER SUSPENSION HOLDER 1° - REAR
XRAY 1° — 0mm ☐ ☐ 1mm
Rasing the suspension holders with shims.

FRONT CAMBER /°
GLUING SIDEWALL YES ☐ ☐ NO
DIFF HEIGHT
REAR CAMBER /°
RIDE HEIGHT /mm
RIDE HEIGHT #107721 GAUGE /mm RIDE HEIGHT

ARM MOUNT BALANCE
#293085 HUDY Pure Tungsten Weight - 10g.
LOWER ECCENTRIC SHOCK BALL FRONT ☐ ☐ REAR
BALANCE /g
ARM SHIM /mm
FRONT ARM: MEDIUM ☐ HARD ☐ GRAPHITE ☐
ARM TYPE: KIT ☐ SOLID ☐
SERVO WEIGHT: STANDARD ☐ LOW PROFILE ☐
ELECTRONICS PLATE: NO ☐ GRAPHITE ☐ WEIGHT ☐
REAR ARM: MEDIUM ☐ HARD ☐ GRAPHITE ☐
ARM TYPE: KIT ☐ SOLID ☐

reset all