

RACE **Basic for CARPET**

TRACK

NAME **XRAY** DATE

LAPS BEST LAP TIME sec

QUALIFYING POSITION FINAL POSITION

TRACK

SIZE OPEN MEDIUM TIGHT

TRACTION VERY-LOW MEDIUM VERY-HIGH

SURFACE SMOOTH MEDIUM BUMPY

TYPE CLAY CARPET ASTRO

CONDITION BLUE GROOVE HARD PACKED DRY
 DUSTY LOAMY WET

DIFFERENTIAL TYPE

FRONT ↓	MIDDLE ↓	REAR ↓
GEAR <input checked="" type="checkbox"/> DIFF ACTIVE <input type="checkbox"/> DIFF 60° 90° 120°	SLIPPER <input checked="" type="checkbox"/> <input type="checkbox"/> SOLID GEAR <input type="checkbox"/> DIFF ACTIVE <input type="checkbox"/> DIFF 60° 90° 120°	GEAR <input checked="" type="checkbox"/> DIFF ACTIVE <input type="checkbox"/> DIFF 60° 90° 120°
OIL 40K cst	OIL cst	OIL 30K cst

SATELLITE GEARS

COMP	COMP	COMP
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
STEEL <input checked="" type="checkbox"/> O-RING	STEEL <input type="checkbox"/> O-RING	STEEL <input checked="" type="checkbox"/> O-RING
40T <input checked="" type="checkbox"/> 41T	CROWN GEAR	40T <input checked="" type="checkbox"/> 41T

CENTRAL SLIPPER & ONE-WAY SETTING

SLIPPING

ONE-WAY TIGHTNESS

PLATES 13 mm

VENTILATED LOOSE

1 CW TURN (BASIC SETUP) FULLY TIGHTEN

GEARING

PINION 1 81 SPUR GEAR

SHOCKS

FRONT	SPRINGS	REAR
4 dots	OIL	4 dots
cst 350		cst 300
2 HOLES <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> 2 HOLES	ø1.6mm <input type="checkbox"/> <input checked="" type="checkbox"/> ø1.8mm	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> 2 HOLES
Holes ø mm		Holes ø mm
KIT <input checked="" type="checkbox"/> 2.0mm Precision	PISTON THICKNESS <input checked="" type="checkbox"/> 2.0mm <input type="checkbox"/> 2.5mm	KIT <input type="checkbox"/> 2.0mm Precision
COMPOSITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>	COLLAR <input checked="" type="checkbox"/> <input type="checkbox"/>	COMPOSITE <input type="checkbox"/> ALU <input checked="" type="checkbox"/>
+4mm +2mm 0mm	BALL JOINT	0mm +2mm +4mm

ANTI ROLL BAR

FRONT **1.8** mm THICKNESS REAR **1.8** mm

TIRES

FRONT BRAND COMPOUND INSERTS WHEELS REAR

ELECTRONICS

MOTOR MOTOR TIMING SPEEDO BATTERY

BODY LIGHT **TOTAL WEIGHT** /g

COMMENTS

